

AEROSEAL®

Adhesive for **AEROFLEX®** Insulation

*Strong, Firm and
Permanent Bonding*



AEROSEAL®

Adhesive for bonding **AEROFLEX®** closed cell elastomeric insulation

AEROSEAL is a Modified Neoprene Contact Adhesive specially formulated for bonding Aeroflex Insulating Materials firmly together. Also, ideal for use with other materials like Metal (painted/unpainted), Cork Board, Polyurethane Foam Rigid PVC Sheet, Formica and Melamine Board and Rubber Sheet.

The high water vapor resistance and good weathering properties of **AEROSEAL** can prevent water or moisture from penetrating through the joining points.

AEROSEAL is able to form a strong, firm and permanent bonding between the applied materials providing long lasting service.



APPLICATION

1. Surfaces of materials to apply should be dry, clean and free from dust, grit, oil, grease or any other loose materials.
2. Stir **AEROSEAL** well before applying a thin and even coat of **AEROSEAL** onto both joining surfaces by using a short hair brush, spreader or metal blade.
3. Allow solvents content of **AEROSEAL** to evaporate until the adhesive becomes dry to touch, but tacky, before joining the materials together normally 5-30 minutes.
4. Bonding is possible within 2 minutes after application if used on absorbent or permeable materials such as, Aeroflex Insulation, cork board and chipboard. If applied on non-absorbent or non-permeable materials like rubber or metal, a minimum of 5 minutes should be allowed to elapse before the surfaces can be bonded.
5. Press the surfaces to be bonded together under firm pressure.

PROPERTIES

Appearance	Black viscous liquid
Total Solids	22±2%
Viscosity at 30°C	3500 - 4500 Cps
Specific Gravity	0.88 - 0.90
Coverage (apply adhesive Both surfaces)	130 – 180 ft ² (3 – 4.5 m ² /liter)
Bond Strength at Open Time 5-15 min.	Min 1.25kg/cm ²

STORAGE AND SHELF LIFE

AEROSEAL can be preserved for at least six months in well sealed containers.

Recommended storage temperature range from +5°C to +35°C. Avoid keeping **AEROSEAL** under conditions that are out of the recommended storage temperature range.

HEALTH AND SAFETY

Advisable to work in well ventilated areas to avoid inhalation of vapor from solvents. The solvents contained in **AEROSEAL** are inflammable and subjected to legislation regulating their storage and use. Keep away from fire and materials which may cause fire such as paper, cloth, plastic etc. **AEROSEAL** contents flammable liquid but dried material is an self-extinguish adhesive.



จัดจำหน่ายโดย : บริษัท เคเอ็มเอ็น ฟอัม จำกัด

KMN
PE-FOAM

215/51 ม.11 ต.หนองปรือ อ.บางละมุง จ.ชลบุรี 20150
Tel.038-231014 / 093-1349667
E-mail : kmnpe@kmnpefoam.com
WWW.KMNPEFOAM.COM

